

WHEELCHAIR ACCESSIBLE VEHICLES

Hackney Carriage Vehicle Licences will not be issued to vehicles being presented to be licensed to carry 5 or more passengers unless such vehicles are immediately wheelchair accessible (i.e. the vehicle must be capable of accommodating a disabled passenger whilst seated in his/her wheelchair). The requirement to remove seats in order to accommodate a wheelchair will not be accepted; seats which fold to allow a wheelchair to be accommodated will be accepted.

This Authority's minimum requirements with regard to a wheelchair accessible vehicle are:-

- (a) That it can accommodate a disabled passenger whilst seated in his/her wheelchair (there must be adequate headroom for the passenger). For this purpose a "wheelchair" is a reference wheelchair as defined in The Public Service Vehicles Accessibility Regulations 2000.

The dimensions for a reference wheelchair are defined as having

- total length of 1200mm, including extra-long footplates
 - total width of 700mm
 - sitting height (from ground to top of head) of 1350mm
 - height of footrest above floor of 150mm
- (b) That the rear/side door used for wheelchair access must be capable of opening as wide as the aperture. A single rear door must be open to a minimum of 90 degrees and for twin rear doors both must open to a minimum of 90 degrees.
- (c) The doorway should provide a minimum of 1220mm in its central third measured from the upper centre of the aperture to a point directly below on either the upper face of the fully raised lift platform or the upper face of the ramp fully deployed on ground level . The door aperture must be wide enough to accommodate a reference wheelchair and have a minimum width of 740mm of unobstructed space.
- (d) There should be sufficient space within the vehicle to accommodate a reference wheelchair. The floor area required for the wheelchair should be at least 750mm x 1250mm with minimum headroom over the area of 1350mm. There must be sufficient space, where applicable, to turn the wheelchair.
- (e) All wheelchair tracking must be fit for purpose and structurally sound.
- (f) A system for securing the occupant in the wheel chair and a system for effective anchoring of wheelchairs shall be provided within the vehicle in all spaces designated as wheelchair space. Wheelchair anchorage systems and devices must conform to European Directive 76/115 EEC (as amended). Additional hand-holds and a step should be provided
- (g) Either a purpose designed wheelchair access ramp or a purpose designed wheelchair lift must be provided.
- (h) Any purpose designed wheelchair access ramp that is carried must be lightweight and easy to

deploy. The ramp shall have visible reference to a safe working load of at least 250kgs and reference that it is certified to BS 6109. Ramps must be capable of being securely fitted when in use and securely installed in the designated storage area at all other times. Ramps must be free from damage, deformity and sharp edges etc. Ramps must be provided with an anti-slip covering.

- (i) Any purpose designed wheelchair lift shall conform to the Lifting Operations and Lifting Equipment Regulations 1998 (LOLER). A report, confirming that the lifting equipment is safe to use shall be presented at the time the annual and 6 monthly vehicle inspection certificate is provided to the council. Vehicles will require a certificate that is valid for a period of 6 months from the date of issue. The lift must be capable of being secured in a suitable and satisfactory position when the vehicle is in motion.
- (j) Vehicles shall comply in all respects, and at all times, with current road traffic legislation.
- (k) Vehicles shall comply with the European Community M1 type approval for passenger carrying vehicles. The definition of category M1 type approval is any motor vehicle with at least 4 wheels designed and constructed for the carriage of passengers.
- (l) Vehicles that have been originally classified as complying with M1 type approval but have undergone modifications or conversions since original manufacture will be considered suitable provided they are presented with the relevant Individual Vehicle Approval (IVA) or Single Vehicle Approval (SVA) certificate or equivalent issued by the Driver and Vehicle Standards Agency (DVSA).
- (m) Any wheelchair accessible vehicle originally given European Community N type approval will be considered unfit for the purpose and will not be considered suitable to be licensed. The definition of a category N type approval is any motor vehicles with at least four wheels designed and constructed for the carriage of goods.

Grandfather rights will apply to vehicles already licensed by the date on which this policy comes into effect. They will be allowed to continue until the end of their useful life, subject to their compliance with all relevant test and inspection requirements.

Once a vehicle licence has expired then Grandfather rights will no longer apply. Applicants wishing to re-licence that vehicle in the future will be required to adhere to the above Wheelchair Accessible Policy requirements.

Vehicles which have been licensed for private hire and not identified as wheelchair accessible must adhere to the above Wheelchair Accessible Policy if they wish to be licensed as a Hackney Carriage Vehicle.

*Grandfather rights do not apply with respect to requirement that ramps are indelibly marked with the vehicle registration number.